

THICK MS-TH 4NR 20 S FOR HILTI S (M16x<>)

- 600 DIAMETER, 400 LONG (MINIMUM) HDPE TWINWALL PIPE, INFILL WITH 25/30 MASS CONCRETE.

FOUNDATION DETAIL (Scale 1:20)

PLAN

TIMBER SCHEDULE

DIAMETER (MIN)
250MM

QUANTITY
8
8

250MM 200MM 180MM

| 1 6 | 8

250MM 200MM FOUNDATION DETAIL
(Scale 1:20)

SECTION

ALL METALWORK, INCLUDING BOLTS, WASHERS, BRACKETS ETC TO BE GALVANISED

— 600 DIAMETER, 400 LONG (MINIMUM) HDPE TWINWALL PIPE, INFILL WITH 25/30 MASS CONCRETE WITH A MAXIMUM AGGREGATE SIZE OF 20MM.

200x200x12 THICK MS
FIN PLATE, 6MM FW
TO BEARING PLATE, 2NR
22 DIAMETER HOLES FOR
22 NR M20 BOLTS, GRADE 8.8

50

CONSULTING ENGINEERS DAMcC 1:50 & 25.07.18 20 KWA/18063/001

KWA
Consulting Engineers
Ward Cottage, Boggan Bank,
Burn Place, Dingwall
IV15 9NQ

PLANS AND **SECTIONS**

STRUCTURAL MAGGS WOOD PROPOSED LOG EVANTON SHELTER EVANTON WOOD COMMUNITY COMPANY